

DISTINCTION SERIES



AI-3000

DISTINCTION SERIES



TEAC

TEAC EUROPE GmbH
Bahnstrasse 12, 65205 Wiesbaden-Erbenheim, Germany
Phone: 0611-71580 www.teac.de

TEAC CORPORATION
1-47, Ochiai, Tama-shi, Tokyo 206-8530, Japan
Phone: 042-356-9156 www.teac.co.jp

Please note that not all models are available in every countries. Design and specifications subject to change without notice.
© 2011 TEAC Corporation. All Rights Reserved. All text, images, graphics and other materials on this catalogue are subject to the copyright and other intellectual property rights of TEAC Corporation. These materials shall not directly or indirectly be published, reproduced, modified or distributed in any medium. Super Audio CD is a registered trademark. All other brand or product names are trademarks or registered trademarks of their respective holders.

TEAC



AI-1000 Stereo Preamp Amplifier

Output Power:	120W + 120W (4 ohms) 85W + 85W (8 ohms)
Total Harmonic Distortion:	less than 0.01%
Signal-to-Noise Ratio:	100dB (A-weighted)
Frequency Response:	10Hz - 30,000Hz (-0.5dB)
Analogue Audio Inputs:	6 (RCA)
Preout:	1 (RCA)
Headphone Out:	1 (6.3mm)
Speaker Terminals:	1 pair (Binding-post)
Compatible Speaker Impedance:	2-16 ohms
Operation:	230V AC, 50Hz
Power Consumption:	240 W
Dimensions (W x H x D):	435 x 116 x 403 mm
Weight:	10 kg
Colours:	Black, Silver



AI-2000 Stereo Preamp Amplifier

Output Power:	180W + 180W (4 ohms) 125W + 125W (8 ohms)
Total Harmonic Distortion:	less than 0.01%
Signal-to-Noise Ratio:	102dB (A-weighted)
Frequency Response:	10Hz - 30,000Hz (-0.5dB)
Balanced Analogue Audio Input:	1 (XLR)
Analogue Audio Inputs:	5 (RCA)
Preout:	1 (RCA)
Headphone Out:	1 (6.3mm)
Speaker Terminals:	2 pairs (Binding-post)
Compatible Speaker Impedance:	2-16 ohms
A/B Speaker Output:	Yes
Operation:	230V AC, 50Hz
Power Consumption:	330 W
Dimensions (W x H x D):	435 x 154 x 403 mm
Weight:	14 kg
Colours:	Black, Silver



AI-3000 Stereo Preamp Amplifier

Output Power:	300W + 300W (4 ohms) 200W + 200W (8 ohms)
Total Harmonic Distortion:	less than 0.01%
Signal-to-Noise Ratio:	102dB (A-weighted)
Frequency Response:	10Hz - 30,000Hz (-0.5dB)
Balanced Analogue Audio Input:	2 (XLR)
Analogue Audio Inputs:	5 (RCA)
Preout:	1 (RCA)
Headphone Out:	1 (6.3mm)
Speaker Terminals:	2 pairs (Binding-post)
Compatible Speaker Impedance:	2-16 ohms
A/B Speaker Output:	Yes
Operation:	230V AC, 50Hz
Power Consumption:	570 W
Dimensions (W x H x D):	435 x 230 x 520 mm
Weight:	31.3 kg
Colours:	Black, Silver



CD-1000 CD/Super Audio CD Player

Supported Disc:	Super Audio CD, CD-DA, CD-R/RW
Dynamic Range:	more than 100dB
Signal-to-Noise Ratio:	more than 110dB
Total Harmonic Distortion:	less than 0.0015%
D/A Converter:	24bit/192kHz D/A Converter
Audio Output:	1 (RCA)
Digital Audio Output:	1 (Coaxial)
Display:	Fluorescent Display
Operation:	230V AC, 50Hz
Power Consumption:	14 W
Dimensions (W x H x D):	435 x 116 x 366 mm
Weight:	7.2 kg
Colours:	Black, Silver



CD-2000 CD/Super Audio CD Player

Supported Disc:	Super Audio CD, CD-DA, CD-R/RW
Dynamic Range:	more than 100dB
Signal-to-Noise Ratio:	more than 110dB
Total Harmonic Distortion:	less than 0.0015%
D/A Converter:	24bit/192kHz D/A Converter
USB Audio Input:	1 (USB 2.0, High-speed)
Balanced Analogue Audio Output:	1 (XLR)
Audio Output:	1 (RCA)
Digital Audio Output:	1 (Coaxial)
Display:	Fluorescent Display
Operation:	230V AC, 50Hz
Power Consumption:	14 W
Dimensions (W x H x D):	435 x 116 x 366 mm
Weight:	7.2 kg
Colours:	Black, Silver



CD-3000 CD/Super Audio CD Player

Supported Disc:	Super Audio CD, CD-DA, CD-R/RW
Dynamic Range:	more than 120dB (24bit) more than 100dB (16bit)
Signal-to-Noise Ratio:	more than 110dB
Total Harmonic Distortion:	less than 0.0012%
D/A Converter:	Dual 24bit/192kHz D/A Converters
Up-conversion:	up to 192kHz
USB Audio Input:	1 (USB 2.0, High-speed)
Digital Audio Input:	1 (Coaxial)
Balanced Analogue Audio Output:	1 (XLR)
Audio Output:	1 (RCA)
Digital Audio Output:	1 (Coaxial)
Display:	Fluorescent Display
Operation:	230V AC, 50Hz
Power Consumption:	18 W
Dimensions (W x H x D):	435 x 116 x 371 mm
Weight:	10.3 kg
Colours:	Black, Silver



TU-1000 AM/FM Stereo Tuner

Tuner:	PLL Synthesised Tuner
Band:	AM, FM with RDS
Signal-to-Noise Ratio:	more than 66dB (FM, Mono) more than 60dB (FM, Stereo)
Preset Station Memory:	50 FM + 30 AM
Audio Output:	1 (RCA)
Display:	Fluorescent Display
Operation:	230V AC, 50Hz
Power Consumption:	4.5 W
Dimensions (W x H x D):	435 x 84 x 331 mm
Weight:	5.2 kg
Colours:	Black, Silver